

M24LR-DISCOVERY

(Start KIT) STMicroelectronics



STMicroelectronics

(STM8, STM32, SPC56, STPM),
(MEMS) EEPROM.

STM

EEPROM

(I²C, Microwire, SPI)

(1,6 5,5),

(1 2 ,

SPI 20 , I²C 1).

(, ,),

WLCSP, 4000000 200

M24LR-DISCOVERY –

EEPROM

M24LRxx

: I²C

RFID

13.56

: M24LR RF

Figure 1. M24LR board and RF transceiver board



M24LR board



RF transceiver board

:

- M24LR
 - M24LR04E-RMN6T/2 EEPROM I²C ISO/IEC 15693 RF ,
4 EEPROM c ;
 - STM8L152C6T6 8- , 8 Flash ;
 - STTS751-0WB3F, ;
 - 20 x 40 PCB ;
 - (User and Reset);
 - SWIM ;
 - I²C ;
 - LCD (24 4).
- RF-
 - CR95HF-VMD5T 13.56 , SPI/UART;
 - STM32F103CB 32- , 128 Flash- ;
 - 47 34 13,56 ;
 - USB .

RFID , ,

M24LRxx -

(, ,), ,

: [M24LR-DISCOVERY](#).

STM

: (044) 230 01 86

e-mail: veber@i-p.com.ua